


**CRANE**

1/4" to 3"

**No. 212 P**  
**Union Bonnet Threaded**  
**Composition Disc**  
**No. 130, UL-Listed**  
**400 PSI Non-Shock**  
**LP Gases @ 150 F**  
**Plug Type Disc**

**No. 212P**

**200 SP**  
**400 WOG**

- No. 130 is excellent in services handling light oils, gasoline, compressed air, volatile fluids, and commercial forms of LP gases such as butane, iso-butane, propane and butylenes up to a limit of 400 psi non-shock 150° F. Gases can be handled separately or mixed, and in liquid or gaseous state.
- No. 130 is air tested and listed by Underwriters' Laboratories, Inc. for handling LP gases provided the system is limited to 250 PSI maximum pressure. It is also suitable for non-shock water service up to 400 PSI 200° F.
- No 212P is ideal for severe service such as throttling, blow-off, boiler feed, soot blower, drip and drain lines; both valves are recommended for steam, non-shock water, oil, gas, or air applications.

Size	Stock Number	
	130	212P
1/4	1085360	1085328
3/8	1085361	1085329
1/2	----	1085330
3/4	----	1085331
1	----	1085332
1 1/4	1085365	1085333
1 1/2	----	1085334
2	----	1085335
2 1/2	----	1085336
3	----	1085337

- Tapered plug type disc on No. 212P is ideal for close regulation of flow. Renewable disc and seat ring are AISI 420-S stainless steel. This specially heat-treated metal offers high resistance to wear, temperature, galling, scoring and corrosion.
- Valves 2" and smaller have a compact union bonnet; 2 1/2" and 3" sizes have a compact bolted bonnet.
- Both valves have a backseat in the interior of the bonnet below the packing.
- Both valves comply with MSS SP-80.

**Ratings, No. 212P**

Temp F.	PSI Non-Shock
-20 to 150°	400
200	375
250	350
300	325
350	300
400	275
450	250
500	225
550	200



1/4" to 3"

**T256AP**

**Union Bonnet**  
**Replaceable Seat and Disc**

**T256AP**

- 200 PSI Saturated Steam to 391°F or 201°C
- 200 PSI Fluid to 550°F or 288°C
- 400 PSI Non-Shock Cold Water, Oil or Gas
- Conforms to MSS SP-80

**200 SP**  
**400 WOG**

Size (In.)	Stock No.
1/4	1080201
3/8	1080202
1/2	1080203
3/4	1080204
1	1080205
1 1/4	1080206
1 1/2	1080207
2	1080208
2 1/2	1080209
3	1080210

**B20**

CONTACT KELLY SUPPLY FOR LATEST PRICING &amp; AVAILABILITY

1-800-KELLYSU (535-5978)