




Bronze Globe Valves Class 300

1/4" TO 3"

No. 382P
Plug Type
Disc
Union Bonnet



No. 382P

300 SP
600 WOG

Temp F.	PSI 1/4" - 2"	PSI 2 1/2" - 3"
-20 to 150	1000	600
200	920	560
250	830	525
300	740	490
350	650	450
400	560	410
450	480	370
500	390	340
550	300	300

Size	Stock Number
1/4	1084420
3/8	1084421
1/2	1084422
3/4	1084423
1	1084424
1 1/4	1084425
1 1/2	1084426
2	1084427
2 1/2	1084428

Ratings Non-Shock

- All sizes are air tested and reliable for exceptionally severe services such as throttling, blow-off, boiler feed, drip and drain lines. Recommended for steam, non-shock water, oil, gas or air.
- Valves feature plug type discs and wide seating surfaces of AISI Type 420-S stainless steel, a heat-treated alloy highly resistant to wear, temperature, galling, scoring and corrosion.
- Size 2" and smaller have union bonnet; 2 1/2" and 3" sizes have bolted bonnets.
- Long lasting Kevlar-graphite composition packing is filled in deep stuffing box with a gland.
- Each valve has a backseat in the interior of the bonnet below the packing.
- Valves comply with MSS SP-80.



1/4" to 3"

T276AP

Union Bonnet

Replaceable Seat and Disc



T276AP

300 SP
600 WOG

- 300 PSI Saturated Steam to 421°F or 216°C
- 300 PSI Fluid to 550°F or 288°C
- 600 PSI Non-Shock Cold Water, Oil or Gas
- Conforms to MSS SP-80

Size (In.)	Stock No.
1/4	1080221
3/8	1080222
1/2	1080223
3/4	1080224
1	1080225
1-1/4	1080226
1-1/2	1080227
2	1080228
2-1/2	1080229
3	1080230



1/4" to 3"

T376AP

Union Bonnet

Replaceable Seat and Full-Plug Disc



T376AP

300 SP
600 WOG

- 300 PSI Saturated Steam to 421°F or 216°C
- 300 PSI Fluid to 550°F or 288°C
- 600 PSI Non-Shock Cold Water, Oil or Gas
- Conforms to MSS SP-80

Size (In.)	Stock No.
1/4	1080261
3/8	1080262
1/2	1080263
3/4	1080264
1	1080265
1-1/4	1080266
1-1/2	1080267
2	1080268