




Bronze Check Valves

Class 200

No. 36 SWING CHECK VALVES 1/4" TO 3"



No. 36

**200 SP
400 WOG**

Ratings

Temp F.	PSI Non-Shock
-20 to 150	400
200	375
250	350
300	325
350	300
400	275
450	250
500	225
550	200

Size	Stock Number
1/4	1083309
3/8	1083310
1/2	1083311
3/4	1083312
1	1083313
1 1/4	1083314
1 1/2	1083315
2	1083316
2 1/2	1083317

**Y Pattern
Regrinding**

No. 36, Threaded

- Excellent for use on steam lines and non-shock water, oil or gas service.
- Y pattern body design provides for minimum pressure drop due to full area flow opening.
- Valve can be reground without removing body from line.
- Install horizontally, or vertically for upward flow, but always with pressure under the disc. An arrow cast on the body indicates correct direction of flow.
- Conforms to MSS SP-80 and Military Spec MIL-V-18436, Style A, Type III valves and with material and design requirements of Federal Spec WWC-V-51F, Class C, Type IV valves.



T453B

1/4" to 3"

**Horizontal Swing
Regrinding Type
Y-Pattern
Renewable Seat and Disc**



T453B

**200 SP
400 WOG**

Size (In.)	Stock No.
1/4	1080041
3/8	1080042
1/2	1080043
3/4	1080044
1	1080045
1-1/4	1080046
1-1/2	1080047
2	1080048
2-1/2	1080049
3	1080050

- 200 PSI Saturated Steam to 391°F or 201°C
- 200 PSI Fluid to 550°F or 288°C
- 400 PSI Non-Shock Cold Water, Oil or Gas
- Conforms to MSS SP-80

Kelly Supply
“The Easier To Do Business With” Company

